

EVINRUDE®



4 HP/2.9 kW

SPECIFICATIONS

ENGINE TYPE	1-CYLINDER/4-STROKE
BORE X STROKE MM (IN)	59 X 45 (2.32 X 1.77)
DISPLACEMENT CC (CU IN)	123 (7.5)
GEAR RATIO	2.15:1
FULL THROTTLE RPM RANGE	4,500 - 5,500 RPM
WEIGHT KG (LBS)*	26 (57)
STARTING	MANUAL
OIL TYPE	NMMA CERTIFIED FC-W® 4-STROKE OIL SAE 10W-30/40 (SF, SG, SH, SJ)
OIL CAPACITY ML (FL. OZ.)	450 (15)
FUEL TANK L	INTEGRAL TANK 1.1
PROPELLER SELECTION RANGE CM (IN)	15.24-22.86 (6-9)
ALTERNATOR OUTPUT	OPTIONAL ACCESSORY: 12V, 60W, 5A
STEERING	TILLER HANDLE
TRIM METHOD	MANUAL TILT
SHAFT LENGTH MM (IN)	381 (15), 508 (20)
WARRANTY	3-YEAR, NON-DECLINING
EMISSIONS COMPLIANCE	CARB 3 STAR

* Weight based on lightest model.